



# Vehicle Positioning System "AND-VPS"

Preventing manipulation in truck scale is a prime need now a days. For this, Altis Industries has integrated vehicle positioning system with the intelligent terminal. AND-VPS is an anti-theft solutions that ensures weighment of properly positioned vehicle only.

"AND-VPS" is a set of special weighbridge intelligent terminal, IR sensors & their mounting accessories.

Besides position checking, other unique features like barr overloading, confidential weighment, empty platform checking are also available to ensure secured weighing process.

#### Features of AND-VPS

- Weighment of properly positioned vehicles only
- Suitable for both pit type and pit less type weighbridge
- Digital inputs for sensing entry, middle and exit position
- 24V operated IR sensor-set
- Easy installation using specially designed poles (mild steels)

#### Basic Hardware Features

- 32 bit ARM processor with sigma delta type 24bit ADC
- Front mount 16x2 LCD display & 0.5inch LED display
- SMPS power supply
- · On board memory to save 1lakh records
- USB ports for Standard computer keyboard & pen drive
- Centronics port for 80 column Dot matrix Printer
- RS232 port for display/GSM modem/ continuous transmission of current weight
- Table top port for connecting external wired displays

#### **Application**

#### Salient Features

- Theft Prevention:-
  - Barring weighment of improper positioned vehicles
  - Keeping track of vehicles passed without weighing
  - Preventing manipulation by loading vehicles back to back
  - Barr overloading according to vehicle type

### Scope of Supply

- AND-VPS
- Pair of IR sensors (2/3 number)
- 24V power supply
- 6 poles

## Software Features "Installation privilege"

- Initial LCD display message field settable as OEM name/weighbridge name
- Installation settings secured under engineer login
- Engineer login password field settable by authorised OEM
- 20 step software calibration with random load sequence
- Smart Calibration
- Multi-step smart calibration
- Calibration data restoring
- · Installation report

### Software Features "Weighbridge privilege"

- Simple process for weighments of Tare/ Gross Vehicle weights
- 10 entries in ticket for 25 characters each
- 4 code banks for 100 codes each (Flexibility of setting)
- Field settable header, footer, signature lines
- Facility to view/print earlier saved records according to RST no/ Vehicle no
- Multiple report option all/summary/filtered/serial no. wise/date wise/time wise
- Dumping of report into pen drive to avail softcopy of records (.xls)
- Field settable Pre-printed tickets
- SMS feature in 3 different ways
- Net weight printing in words
- Mandi Application feature of Rate, Amount, Binding material deduction etc.

#### **Optional Features**

- Confidential Report
- Inbuilt wireless for connecting wireless accessories (IB, display)
- · Graphical LCD display

Processor	32bit ARM Processor
Processor clock frequency	50 MHz
Real time clock	On board battery backed RTC.
RTC Clock frequency	32.768 KHz
Memory	On board memory to save 1 Lakh records
Power supply	SMPS power supply
Input Voltage	90V to 270V AC @ 50Hz
Digital input	3 numbers for connecting output of IR sensor
Protection	* 750mA fuse for input AC mains
	* Input line filter for EMI and RFI suppression
	* Spike suppressor for input transients
	<ul> <li>Opto-isolation of signals and I/Os for high immunity from electricalnoise</li> </ul>
Power Consumption	10 VA (approx.)
Conversion Speed	Internal 25 samples per second
Load cell excitation	8V DC with current capability to drive up to 12 load cells of 350 ohms input resistance
Signal Sensitivity	0.3 micro volt per division of weight (unit weight)
Display	16 characters by 2 line LCD display with backlight for displaying numerals and alphabets & 1/2" LED 7 segment red display to show weight
Keyboard port	101-key with USB connector compatible keyboard. (Recommended for use Logitech or Microsoft)
USB Port	USB Port configured for Pen Drive
Printer port	Isolated Centronics compatible printer port provided on rear panel for connecting 80-column dot matrix printer for printing of weighment record and reports
Serial port	Isolated RS-232 serial port is provided for continuous weight transfer
Remote Display Port	Remote display port is provided to connect optional 1/2inch, 1inch, 2.3inch or 4inch bright red LED display to indicate the weight on the platform
	Operating temperature: 0° to 55° Celsius
Environment	Operating temperature. 0° to 33° Ceisius

#### Sample Ticket

#### ABC WEIGHBRIDGE NEW CITY INDIA VEHICLE NO : MH 09 AB 1234 23 MATERIAL : STEEL SOURCE : NEW CITY CUSTOMER : GAGAN : RODS COMMODITY CHALLAN NO : 9003 DESTINATION : OLD CITY : 89/1 A.B ROAD NEW CITY PHONE NO. : 982751146 ADDRESS REMARK : NA Date:20/08/2015 Time:15:26 Date:20/08/2015 Time:15:25 GROSS Wt: 23915 kg 15880 kg TARE Wt: EIGHT ZERO THREE FIVE kg NET Wt: 8035 kg Charges(1): Rs. 700 Charges(2): Rs. 500 Charges(total): Rs. 1200 OPERATOR'S SIGNATURE: Contact for repairs at tel no

#### Sample Report

						41			DIA	*								
	BRIDGE from RST : IAL STEEL	22	To: 27											Pag	e N	umber	:	1
No ; RS	T   VEHICLE	NO	: CUSTOMER	1	MATERI	;	GROSS kg	;	Date &	Time	;	TARE kg		Date & T	100	; NET k	g :	CHRG
1 :	22 : MP 09 A							;	20/08/2015	15:15	:	7940	:	20/08/2015	15:14	; 794	0 :	700
2	23 ; RH 09 A	9 123	: SAGAN	i	STEEL	;	23915	1	20/08/2015	15:26	1	15880	1	20/03/2015	15:25	: 803	5 ;	1204
3 :	29 ; KA 29 A	B 123	: RAHUL	-	STEEL	:	23915	:	20/08/2015	15:28	,	15885	;	20/09/2015	15:28	: 803	0 ;	1400
5 :	25 ; JK 69 A	8 123	: RAM		STEEL	;	15889	:	20/08/2015	15:29	;	7945	1	20/08/2015	15:30	: 793	5 ;	1200
J (	27 ; JK 12 A	8 123	: AMAN	1	STEEL	:	7940	1	20/08/2015	15:32	:	10	1	20/08/2015	15:32	793	3 :	1200
otal			>													3987	0 :	5700

### Pen Drive dumping Screenshot











